

High-density 1U standard chassis flame-retardant in stock



Overview

Efficiently manage fiber cables with the High-Density IANOS Chassis (1U). Supports up to 12 single or 6 double modules, supports 72 ports per 1U, compatible with EDR, features front/rear module fitting and horizontal opening front door. y and quick installation is required. The enclosure is available in 1RU 144 fiber capacity through LC connector and has various kinds of modules to su igned for MTP, MPO and LC interfaces. up to twelve NextSTEP modules in any combination in any shelf position. NextSTEP modules slide easily into any of the twelve stepped shelf subsequent MACs, and. The Extreme 25G-LR-SFP10KM compatible SFP28 transceiver provides 25GBase-LR throughput up to 10km over single mode fibre (SMF) using a wavelength of 1310nm via an LC duplex connector. The SFP28 transceiver works on the same 10G network cabling Infrastructure, boosting speed by at least 2. The CommScope SYSTIMAX 108356312 FlexiMAX U/UTP High-Density Patch Panel is a 24-port, 1U modular panel designed for structured cable management in networking and telecommunications applications. Built for EIA 19-inch racks, it features a flush rack-mount design with a black powder-coated steel. PPC's Ultra-High Density (UHD) Chassis is a modular, standards-based, pre-terminated distribution platform designed to increase port density, improve connector access, and efficiently utilize valuable rack space in data centers.



Article Content

UHD Chassis Spec Sheet

PPC's Ultra-High Density (UHD) Chassis is a modular, standards-based, pre-terminated distribution platform designed to increase port density, improve connector access, and efficiently utilize valuable

1U Rack Mount Fiber Enclosure Unloaded, Slide-out

Each SFP28 transceiver module is individually tested in targeted switch, it is fully

Copper/Fiber Enclosure for 4 High-Density Cassettes, 1U

The N484-01U is a 19-inch rack-mount chassis that supports up to four high-density copper/fiber cassettes for managing your networking equipment in 1U of space.

Commscope Fleximax U/UTP High Density Panel

Built for EIA 19-inch racks, it features a flush rack-mount design with a black powder-coated steel frame, ensuring durability and professional aesthetics. The panel is unloaded, allowing users to customize

FirstLight Ultra High Density 1U Chassis

FirstLight™ Ultra High Density 1U Chassis Datasheet FirstLight™ 1U Ultra High Density (FL UHD) Chassis is the part of the system for high density fibre optics infrastructure management in Data

Fire Retardant Poly Sheeting in Stock

Uline stocks a wide selection of Fire Retardant Poly Sheeting. Order by 6 p.m. for same day shipping. Huge Catalog! Over 45,000 products in stock. 14 locations

TPS 1U Chassis

TPS 1U Chassis: Compact 19-inch rack mount power supply chassis. Durable, corrosion-resistant, easy to install. Ideal for data centers and industrial use.

Rack-Mount Fiber Enclosure, 18 Units, Steel, Black

Q-Series Fiber Enclosure, Rack-Mount, Gauge: 18, Rack Units: 1U, Steel, 17.12" Wide x 1.72" High x 19.18" Deep, Black The Q-Series fiber enclosure system is designed to support standard density

High Density 1RU 144F Fiber Enclosure

High Density 1RU 144F Fiber Enclosure Molex High Density Fiber Enclosures are designed for high density applications such as Data Centers, SAN, medical healthcare, central offices or any other

1U Rackmount Server Cases | SCAN UK

These rackmount cases are 1U high and are designed for entry-level and high-density servers. Although every case in this category is 19in wide, also make

Choosing the Right Rackmount Server Case: 1U, 2U,

Understand how 1U, 2U, 3U, and 4U rackmount server units vary in order to optimize your server requirements to select the most appropriate piece

1U Rack Mount Fiber Enclosure Types and Selection Guideline

As a necessary fiber cable management component of high-density cabling, the 1U rack mount fiber enclosure is widely used in data centers to house, organize, manage, and protect fiber

Wirewerks Next Step 1RU Rack Mount

The NextSTEP™ 1U High-Density Patch Panel is a major sub-system within the overall NextSTEP Technology™ solution, bringing new levels of flexibility,

FibreFab FirstLight UHD Catalogue Ver3.0 | PDF | Data

FirstLight™ Ultra High Density Chassis are available in 1U, 2U or Zero U options. The system density is industry leading with capacity to house up to 288 LC.

Fiberdyne Labs, Inc. 1U FiberPass HD Cassette Chassis

Fiberdyne Labs' 1U FiberPass HD Cassette Chassis supports Ultra High Density Fiber Distribution Environments.

4 panel (1U) Rack Mount UHD Chassis Patch Panel | Ships Same

This panel truly provides an ultra high density option for coupling your backbone fiber optic assembly and fiber optic patch cables. You can also mix different types of fiber optic connectors and we offer

1U Rack Mount Fiber Enclosure Unloaded, Slide-out

FS FHZ 1U rack mount fiber optic enclosure holds up to 6 x FHZ MTP cassettes for up to 216 LC fibers, which provides an premium ultra high density solution for

IANOS Standard chassis 1U

Efficiently manage fiber cables with the High-Density IANOS Chassis (1U). Supports up to 12 single or 6 double modules, supports 72 ports per 1U,

Choosing the Right Server Case: 1U, 2U, 3U, and 4U

4U Server Case—This is 7 inches tall, making it the biggest in the comparison. It accommodates high-performance components, effective cooling

Fire Retardant Cable Market Size, Share, Trends & Forecast

The increasing complexity and density of electrical networks in modern buildings demand higher safety standards, fueling market expansion. Critical Restraints & Friction Points Supply Chain

1 RU Q-Series High Density Rack-Mount Fiber Enclosure

The Q-Series High Density Rack Mount fiber enclosure system is designed to support high density applications in data centers and building networks. The all

FTD-1UFX-N, High Density 1U 19" Rack Chassis, Holds up to 9/6/3

The high-density FTD chassis supports flexible configurations with full capacity for 9× 4CH, 6× 8CH, or 3× 16CH Mux/Demux modules, and supports the flexibility to install Mux/Demux modules with

RS112PS18M Rugged 1U Carbon Fiber Server

An ultra-lightweight chassis providing EMI/EMC protection and shock and vibration resilience makes the RS112PS18M a popular choice for applications in extreme environments.

Choose the Perfect Rackmount Server Case: 1U to 4U

Choose 1U server chassis for maximum density and space-constrained environments with lower performance and expansion needs. Opt for

Tripp Lite N484-01U Tripp Lite High Density Copper Fiber Enclosure ...

Tripp Lite's N484-01U is a 19" rackmountable chassis that supports up to 4 High Density Copper / Fiber cassettes for managing your networking equipment in a single 1U of space. Choose amongst a wide

Fire Retardant Netting

Use Redbird Fire Retardant Bird Netting for projects requiring fire retardant products that meet NFPA 701 standards. Redbird Fire Retardant Bird Netting is

Supermicro 1024US-TRT Server Review: 128 Cores in a 1U Chassis

Supermicro designed this slim 1U dual-socket server for high-density environments in enterprise applications, high-end cloud

High Density 1U Rack Mount Modular Enclosure for FTTH

High Density 1U MPO Modular Enclosure Unshielded Unloaded Rack Mount FTTH 4X FHD Cassettes 144 Fibers 8 Fiber Optic Equipment 5.0 (4 reviews) 10 sold Complies with EU standards

Rack-mount chassis for 4 high-density fiber or copper

1U rack-mount enclosure panel allows you to add up to 4 high-density copper or fiber cassettes to your rack installation.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://kwsaevents.co.za>

Email: sales@kwsaevents.co.za

Phone: +27 21 852 4719

Address: 25 Riebeek Street, Cape Town, 8001, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

